



# **NEYORO 28A**

## **MSDS Number**

BJBLJ

## **National Stock Number**

6520-00F012020

## **Product Name**

**NEYORO 28A** 

#### Manufacturer

J M NEY CO

## **Product Identification**

Product ID:NEYORO 28A MSDS Date:01/01/1987 FSC:6520 NIIN:00F012020 MSDS Number: BJBLJ

# **Responsible Party**

J. M. NEY CO.

**NEY INDUSTRIAL PARK** 

BLOOMFIELD, CT 06002

US

Emergency Phone: (203) 242-2281

Info Phone: (203) 242-2281

Cage: FO553

## **Contractor**

NEY J M CO DENTAL DIVISION

BLOOMFIELD, CT 06002

US

(203) 242-2281 Cage: 6M651

# **Ingredients**

SILVER (SARA III)

CAS: 7440-22-4

RTECS: VW3500000

Fraction By Weight: 22%

OSHA PEL0.01 MG/M3

ACGIH TLV: 0.1 MG/M3; 9192

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

NICKEL (SARA III)

CAS: 7440-02-0

RTECS: QR5950000

Fraction By Weight: 3%





OSHA PEL1 MG/M3

ACGIH TLV: 1 MG/M3; 9192

#### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: NO

Health Hazards Acute and Chronic: PRODUCT IS NOT A HAZARD AS SUPPLIED. DUST, MISTS OR FUMES MAY BE GENERATED WHEN CUTTING, GRINDING, SOLDERING OR WELDING. SKIN: GRAY PIGMENTATION, CUTS, BURNS, & DERMATITIS.

Explanation of Carcinogenicity: NICKEL IS AN ANIMAL CARCINOGEN.

Effects of Overexposure: AS SUPPLIED, PRODUCT IS NOT CONSIDERED TO BE

TOXIC. SKIN: GRAY PIGMENTATION, CUTS, BURNS, & DERMATITIS.

#### First Aid

First Aid: INHALATION: REMOVE FROM EXPOSURE & OBTAIN PROMPT MEDICAL ATTENTION.

## Fire Fighting

Fire Fighting Procedures: SILVER DUST IS A MODERATE EXPLOSION HAZARD.

## **Accidental Release**

Spill Release Procedures: IF LARGE QUANTITIES OF DUST ARE GENERATED, USE INDUSTRIAL VACUUM TO CLEAN UP. MOLTEN METAL SHOULD BE ALLOWED TO SOLIDIFY BEFORE CLEAN UP.

## Handling

Handling and Storage Precautions: PROVIDE PROTECTIVE EQUIPMENT WHEN CUTTING, GRINDING, SOLDERING, WELDING, MELTING, MACHINING & HANDLING OF NON-FERROUS METALS.

#### **Exposure Controls**

Respiratory Protection: WEAR WHEN CUTTING, GRINDING, SOLDERING OR WELDING

Ventilation:LOCAL EXHAUST TO KEEP DUST, MIST OR FUMES BELOW TLV Protective Gloves: RECOMMENDED WHEN GRINDING OR MELTING

Eye Protection: RECOMMENDED Supplemental Safety and Health

ALLOY PRODUCTS ARE SOLID METALS SHAPED AS WIRE, PLATE, STRIP OR IN FINISHED FORMS AS INGOTS, NUGGETS, ELECTRICAL CONTACT ASSEMBLIES, SWITCHES, OR AS OTHER FORMS FOR ELECTRONIC & DENTAL USE.

## **Chemical Properties**

Solubility in Water: NONE

Appearance and Odor: SOLID METAL-WIRE, PLATE, STRIP, INGOTS, NUGGETS

## **Stability**

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products: WELDING FUMES

## Disposal

Waste Disposal Methods: DISPOSAL OF DUST USING APPROVED METHODS CONSISTANT W/APPLICABLE LOCAL, STATE, & FEDERAL REGULATIONS. MOLTEN METAL SHOULD BE RECLAIMED USING STANDARD INDUSTRIAL PRACTICES SUCH AS REMELTING & REFINING.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.